

Capacity in Tons (NKH FSP)	30	50	100	150	200	300	400	500
Dia of Screw	3.25"	4"	5"	6"	6.5"	8"	9.5"	11"
Stroke of Press	8"	9"	11"	14"	15"	17"	19"	21"
Table of Slide (maximum)	14"	15"	19"	22"	23"	26"	29"	33"
Table of Slide (Minimum)	6"	6"	7"	8"	8"	9"	10"	12"
Size of Table (Front)	12" x 11"	15" x 14"	19" x 18"	21" x 20"	22" x 21"	25" x 24"	28" x 28"	30" x 30"
Distance Between Table to build	6"	6"	8"	10"	10"	12"	14"	16"
Distance Between Colomns	13"	16"	20"	22"	23"	26"	30"	32"
Distance Between Guides	9"	12"	14"	16"	17"	19"	22"	24"
Bore in Table	3"	3"	4"	5"	5"	6"	6"	6"
Bore in Ram (Shank Dia)	1.5"	1.5"	2"	2.5"	2.5"	3"	3"	4"
Height of Press	9" x 9"	12" x 12"	14" x 14"	16" x 16"	17" x 17"	19" x 19"	22" x 22"	24" x 24"
Motor Power Required in H.P.	5/8"	5/8"	5/8"	3/4"	3/4"	1"	1"	1.25"
R.P.M.	5/8"	5/8"	5/8"	5/8"	5/8"	3/4"	1"	1"
Table of Slide (maximum)	5	7.5	10	15	20	30	40	50
Table of Slide (Minimum)	1440	1440	960	960	960	960	960	960
Distance Between Table to build	8" - 6"	9" - 6"	10" - 6"	12" / 6"	12" - 6"	14" - 8"	15" - 8"	17" - 6"
Distance Between Colomns								
Distance Between Guides								
Bore in Table								
Bore in Ram (Shank Dia)								
Ram.								
T Slot in Table								
T Slot in Ram								
Motor Power Required in H.P.								
R.P.M.								
Height of Press								
All Sizes are in inches	All Sizes are subjected to change without prior notice due to regular improvement							